(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



| 1800| | CHIND | CHIND | CON 1111 | CON 111

(43) International Publication Date 11 November 2004 (11.11.2004)

PCT

(10) International Publication Number WO 2004/097892 A2

(51) International Patent Classification7:

H01J 61/00

(21) International Application Number:

PCT/IB2004/050541

- (22) International Filing Date: 28 April 2004 (28.04.2004)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 03101204.0


1 May 2003 (01.05.2003) E

- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): WELTERS, Wilhelmus, J., J. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). SCHUITEMAN, Marten, W. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

- (74) Agent: PET, Robert, J.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, BB, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD OF MANUFACTURING A LAMP



(57) Abstract: Method of manufacturing a lamp comprising a transparent vessel containing a gas filling, a luminous element or an electrode extending inside the vessel and connected to a lead wire extending through a pinched portion of the vessel, which lead wire is provided with a protective coating obtained by applying a liquid to the outside of the pinched portion where the lead wire extends from said pinched portion, characterized in that said liquid is a solution of a compound comprising a positive ion of a material chosen for its propensity to react with oxidized lead wire material so as to form the protective coating.